# MILLENIUM 1675.8MLG/MSG + i

#### **DESIGN**

The MILLENIUM range of attractive ergonomically-designed rotisseries, boasts a number of innovative features for increased functionality and are an ideal show-piece used throughout the world in hotels, restaurants and deli stores.

The naked flame from Rotisol's patented burners lick the cast iron hearth creating a spectacular visual, whilst being safe and simple to operate and easy to clean. Spits are driven by individual motors rotating at 2 ½ times per minute allowing meat or poultry to constantly baste itself, sealing in natural juices and cooking to perfection.

### **FEATURES**

- ☐ Energy Efficient
- ☐ Independent motors
- 4 tempered glass doors
- ☐ Safety with installed thermocouple
- ☐ Equipped with bottom drip tray with drainage tap
- Powerful halogen lamp.




Black and brass finish



## **FINISHES**

Standard model in black enamel. A choice of other colours are available. Choses a colour scheme for Millenium.



With chrome or brass trims.



#### **ACCESSORIES**

A variety of accessories are available for the unit. Video of available accessories and video of vertical spit system.


CUI1675 Anti-cutting prongless spit.		BP1675 Chicken spit.	<del>LIII</del>	BRC1675 Basket spit.	
BS1675 Sabre spit for ham / turkey.	+	BRRO1675 Roast-clamp spit.		BA1675 Lamb/suckling- pig spit.	X
GCP1675 Spare rib rack.		GSV1675 Raised rack for meat storage.		PID1675 Stainless steel tray to unspit.	



# MILLENIUM 1675.8MLG/MSG + i

#### Front view Side view Rotisserie with roof (optional) Rotisserie with roof (optional) and base on casters (optional) and base on casters (optional) (lamps 2x25W) 1680 Illuminated Sign **ROTISSERIE** (Optional) Protective Roof (Optional) 90 1725 GRANDES FLAMMES MILLENIUM • **(** • securit • glass 1645 doors 1620 **(** Electrical and Gas Connection, in rear . **(** n Ħ Base (Optional) 655 1675 195 Ħ 1675 605 Custom Base Cabinet (Optional) Ŋ

#### Top view Rotisserie with roof (optional) and base on casters (optional)





Stainless steel finish



# **SPECIFICATIONS**

Gas Power	Natural : 140000 BTU/h ; Propane : 128000 BTU/h.		
Gas minimum pressure	Natural : 17,4 mbar. Propane : 27,4 mbar.		
Gas connector	³¾" male		
Electricity	208-230 Volts 1 phase + neutral + earth		
Capacity	56/64 poultries		
Warranty	1 year parts and labor		
Venting	Hood installed conformly with all local codes		
Minimum clearance	21/2" on the right, left and rear side		
Shipping weight	350 kg		

Revised: February 2017

# **Celco** Inc.

### www.celco.ca

585 Secretariat Court, Mississauga, Ontario, L5S 2A5 (905) 364-5200 1-866-77CELCO (23526) info@celco.ca

#### **Rotisol S.A.S.**

Zone industrielle La Trentaine, Avenue Gustave Eiffel 77507 Chelles cedex - FRANCE

s.bennell@rotisol.com - Tel: +33 1 64 21 80 00

www.rotisol.com