

Interior cabinet walls are constructed of white epoxy coated steel liner with full hi-level stainless steel coved corner floor.

Exterior cabinet construction consists of full stainless steel front and sides.

Efficient condensate hot gas loop built into condensate pan for energy saving evaporation of excess condensate water.

All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas.

Two adjustable, heavy-duty epoxy coated wire shelves.

All units come standard with heavy-duty worktop surface.

Vaulted self closing door that remains open at 90 degrees.

Easy to mount plate casters (two lockable) are standard with all units.



Electronic thermostat with external digital LED display for accurate control and easy reading.

Environmentally friendly R290 Hydrocarbon gas.

Magnetic door gasket is removable and replaceable without tools.

Larger fan motor and blades for more efficient air flow ensuring faster recovery times.

Solid door construction with foamed-in-place recessed handle.

Tested to NSF Standard 7 requirements for food storage.

Standard with full three-year parts and labour warranties and a five-year compressor warranty.

Model	Refrigerant	Number Of Doors	Number Of Shelves	Capacity (CU-FT)	HP	Voltage	Amps	Nema	Dimensions (Inches) W x D x H	Shipping Weight
CUC72RW	R290	3	3	18	3/8	115/60/1	3.5	5-15P	71.73 x 29.92 x 39.45	357lbs

