DESIGN

The PERFORMANCES range of rotisseries have been especially designed for volume cooking with high output, speed and cooking quality.

Well designed, user friendly and reliable the PERFORMANCES is used by leading supermarkets and chain restaurants throughout the world.

Conscious of the cost involved for our clients, the PERFORMANCES rotisserie has energy saving infrared burners, patented by Rotisol, that enables the rapid roasting of a variety of products.

FEATURES

- Independent motors
- Optional lighting
- ☐ Removable inner side panels for cleaning
- ☐ Independent infrared burners with interchangeable ceramic bricks
- ☐ 2 tempered glass doors
- Optional personalised removable roof signage
- ☐ Equipped with bottom drip tray with drainage tap

FINISHES

Standard model in finished STAINLESS STEEL. A choice of front coloured panels are available.





Black front panels and stainless steel finish



ACCESSORIES

A variety of accessories are available for the unit. Video of available accessories and video of vertical spit system.

CUI1160 Anti-cutting prongless spit.		BP1160 Chicken spit.	LIII	BRC1160 Basket spit.	
BS1160 Sabre spit for ham / turkey.	+	BRRO1160 Roast-clamp spit.		BA1160 Lamb/suckling- pig spit.	
BCR1160 Spatchcock chicken spit.	A supply the supply of the sup	DEC Spit mover.		AT Gas lighter.	




PERFORMANCES

1160.6PG/PiG

Front view Side view Rotisserie with roof (optional) Rotisserie with roof (optional) and base on casters (optional) and base on casters (optional) (lamps 2x25W) 1145 Illuminated Sign <u> POTISSERI</u>E (Optional) Protective Roof (Optional) 90 450 0 **PERFORMANCE** 0 securit glass doors 0 Electrical and Gas • Connection, in rear 602 1145 520 Caster Base (Optional) 1145 Heated Base Cabinet or Base Cabinet •

Top view Rotisserie with roof (optional) and base on casters (optional)





Stainless steel finish



Revised: February 2017

SPECIFICATIONS

5. <u>14. 14. 119.13</u>				
Gas Power	Natural : 61500 BTU/h ; Propane : 56500 BTU/h.			
Gas minimum pressure	Natural : 17,4 mbar. Propane : 27,4 mbar.			
Gas connector	³¼" male			
Electricity	208-230 Volts 1 phase + neutral + earth			
Capacity	24/30 poultries			
Warrantly	1 year parts and labor			
Venting	Hood installed conformly with all local codes			
Minimum clearance	2 ^{1/2} " on the right, left and rear side			
Shipping weight	150 kg			

DISTRIBUTOR

Celco Inc.

www.celco.ca

585 Secretariat Court, Mississauga, Ontario, L5S 2A5 (905) 364-5200 1-866-77CELCO (23526) info@celco.ca

Rotisol S.A.S.

Zone industrielle La Trentaine, Avenue Gustave Eiffel 77507 Chelles cedex - FRANCE

s.bennell@rotisol.com - Tel: +33 1 64 21 80 00

www.rotisol.com